




Series
MC

Multi-Cal Pressure Calibrator

Interchangeable Ranges, $\pm 0.05\%$ Accuracy, Datalogging Capability, NIST Traceable

TEST EQUIPMENT

Pressure Calibrators



Series MC Portable Multi-Cal Pressure Calibrator performs a wide variety of simple and complex pressure based measurement, test, and calibration operations. Modular sensor design allows user to select pressure measurement range for application flexibility. Calibrator can accommodate up to two interchangeable pressure modules (sold separately below) in any combination of range or accuracy.

Simultaneously display two separate measurements on the two line, alphanumeric display. Readings can be displayed in a choice of 12 preprogrammed engineering units or any single user-defined unit. Calibrator features min/max recall, hi/lo alarm, percentage of full-scale pressure readings, mA/voltage measurement, leak rate and pressure decay measurement, switch testing capabilities, including trip point and deadband, and velocity/volume flow rates.

Quickly document calibration procedures using the data logging feature which stores up to 384 sets of pressure and time/date stamped measurements. Easily upload stored data to an IBM compatible computer via the RS232 port. Calibrators and modules include certification to NIST traceability—ideal as a secondary standard for calibrating pressure equipment.

Multi-Cal Pressure Calibrator includes utility software, test leads, protection module, adjustable hand strap, AC adapter, batteries, instruction manual, and hard carrying case.

APPLICATIONS

Pressure measurement for clean room control, filter performance monitoring, HVAC testing and setup, draft measurement, airflow measurement control, differential pressure measurement in laminar flowhoods, paint booths, industrial ovens and fume hoods. Use as a secondary standard for calibrating pressure equipment.

Multi-Cal Pressure Modules are interchangeable and available in a wide selection of pressure ranges and accuracies. Handheld calibrator accepts up to two pressure modules. Modules include NIST calibration certification.

Model	Range	Price
MC1000	0.25" H ₂ O Differential Pressure, ± 0.07	\$2047.00 (N)
MC1001	0.50" H ₂ O Differential Pressure, ± 0.07	2047.00 (N)
MC1004	5.00" H ₂ O Differential Pressure, ± 0.06	1670.00 (N)
MC1006	25" H ₂ O Differential Pressure, ± 0.06	1670.00 (N)
MC2010	5.0 psig Gauge Pressure, ± 0.05	1349.00 (N)
MC2012	15.0 psig Gauge Pressure, ± 0.05	1349.00 (N)
MC2016	100.0 psig Gage Pressure, ± 0.05	1349.00 (N)

(N) Items are net priced and are not subject to any discount.

OPTIONS

Consult factory for other pressure ranges and accuracies. FM approved models are also available.

SPECIFICATIONS

Service: Clean, dry, nonconductive, noncorrosive gases.

Accuracy: Differential pressure modules: $\pm 0.06\%$ FS; Gauge pressure modules: $\pm 0.05\%$ FS; Voltage input: $\pm 0.025\%$ FS @ 0/10 VDC, $\pm 0.10\%$ FS @ 0/30 VDC; Current input: $\pm 0.03\%$ FS @ 0/20 mA, $\pm 0.05\%$ FS @ 0/50 mA.

Sensitivity: $\pm 0.002\%$ of span with dampening 1 part in 50,000 (max).

Repeatability: Ranges $\leq 0/2$ psi: $\pm 0.05\%$ of span; Ranges $\geq 0/5$ psi: $\pm 0.02\%$ of span.

Output: RS232 serial interface, 9-pin.

Alarm Output: SPST form C 110 VDC, 120 VDC (max), 1 A (max), 30 W, 62.5 VA (resistive).

Display: Alphanumeric LCD, 0.37" (9.5 mm) height per line, 2 lines, 16 characters/line.

Display Update: 100 ms.

Ambient Operating Temperature: 32 to 120°F (0 to 49°C).

Storage Temperature: -4 to 158°F (-20 to 70°C).

Process Connection: 1/8" female NPT.

Electrical Connections: Miniature recessed banana jacks.

Power Requirements: Internal: (2) 9 V alkaline batteries, included, user replaceable and VL1220 or BR1225 lithium metal battery, installed functional, user replaceable; External: AC adapter 9 VDC, 500 mA.

Battery Life: 30 hours (approximate).

Engineering Units: inH₂O, psi, inHg, kPa, mbar, cmH₂O, mmHg, and user-defined.

Overpressure: Differential pressure modules: 50 psi positive direction, 15 psi negative direction; Gauge pressure modules: 2x range (0/5 psi to 0/1000 psi).

Temperature Compensation: 20 to 120°F (-7 to 49°C).

Temperature Error: Maximum of $\pm 0.004\%$ of span per °F over compensated range for zero and span.

Temperature Effect Electrical Measurement: $\pm 0.001\%$ of span per °F over compensated range.

Dampening: (Measurement averaging) programmable from 0 to 16 consecutive readings.

Baud Rate: 300, 1200, 2400, or 9600, selectable.

Housing Material: ABS plastic.

Weight: Calibrator: 2.2 lb (1.3 kg); Pressure module: 0.5 lb (0.3 kg).

Model MC2K, Handheld Calibrator\$3003.00 (N)