



There's just

NO comparison!

PORTABLE

UNIQUE USER-FRIENDLY BENEFITS	QSTAR	Others
Installation and setup is fast and easy — less than five minutes! Quickstart Guide / Online Help / Electronic User's Manual	/	0
Clear, consice Setup menu assures easy operation. User-friendly menu displayed on largest backlit LCD screen.	/	0
Anti-Noise Deflector Technology	/	0
Automatic Fluid Control Technology	/	0
Parameters Calculator (Proprietary) Available via USB drive, Smartphone web app and online. Calculates flowrate accurately based on pipe size and velocity. Includes Reynolds number calculation	~	0
GPI Toll-Free Technical Support Available 8-5 p.m. CST Monday through Friday		0
Heat Resistant (up to 300° F) Transducers Included	/	0
Integrated Heat Quantity Measurement Capabilities (Standard) Heat measurement inputs / Pre-programmed software	/	0
Online Diagnostics Oscilloscope - Signal Strength Analyzer	/	0
Three sets of Transducers cover 1/2" to 240" pipe sizes.	/	0
Cross Correlation Signal Detection	1	0

BEST VALUE BASED ON FEATURES AND COST!



Wichita, KS USA 67220-3205 316-686-7361 | FAX: 316-686-6746 888-996-3837 | www.GPImeters.net