
SHERWOOD VALVE

SUPERIOR REFRIGERATION PRODUCTS

Refrigeration Duty Pressure Relief Valves



The Most Complete Range of Refrigeration Relief Valves

A Variety of Valve Styles to Cover All Your Refrigeration Needs

Sherwood Valve offers a full line of pressure relief valves under its Superior Refrigeration brand. The Superior Pressure Relief valve is available in multiple configurations and connection sizes. Pressure ratings from 150 through 800 PSIG are available in 25 PSIG increments.

Superior design makes the difference!

The Superior valve assembly provides a rugged and reliable sealing system over a high range of temperatures. The molded virgin PTFE Teflon seats are superior to rubber seats. The molded design creates a stable and uniform seal to ensure low refrigerant leakage.


Superior Performance and Safety are Our Top Priorities

All valves have been designed, constructed and rated in accordance with ANSI/ASHRAE 15 Standard Safety Code for Mechanical Refrigeration and the Canadian Standards Association. All Superior Refrigeration valves have ASME certifications. Before any are shipped, all completed valve assemblies are tested twice to assure reliable and repeatability. Each valve is stamped with the U.V./N.B. certification to indicate National Board certifications at rated capacities.



Refrigeration Duty Pressure Relief Valves

- 150 800 psi
- Body Construction: Brass
- Seat Material: 100% Molded PTFE Virgin Teflon
- Spring Material: Stainless Steel
- Minimum/Maximum Temps.: -40°F/325°F
- Initial Leak: Set Pressure ±3%
- Full Discharge: Initial Leak +10%
- Reseat: By 50-70% of set pressure
- Canadian Registration No.: 0G8195
- C.S.A. File No.: LR32768
- N.B. Certificate Nos.
- ASME Certificate No.: 28,516



	Atmos	
	Cata Num	
	300	
	300	
	300	
Ĥ	* Atmosp	

Atmospheric					
0-1-1-1	Size				
Catalog Number	Inlet	Outlet			
Nulliper	NPT	X			
3000	1/8	*			
3001	1/4	*			
3002	3/8	*			

Atmospheric - No External Connection

Size

Outlet

3/8

3/8

1/2

1/2

5/8

Inlet

NPT X SAE

1/4

3/8

3/8

3/8

1/2

Straight Thru

Catalog

Number


3012

3014

3015

3016

3020



Female Connection *						
Cotolog	Size					
Catalog Number	Inlet Outle					
Nulliper	NPT	X FPT				
3030	1/2	1/2				
3031	1/2	3/4 3/4				
3045	3/4					
3060	1	1				
3075	1-1/4	1-1/4				

P	Angle	Size			
	Catalog Number	Inlet	Outlet		
		NPT	X SAE		
	3212	1/4	3/8		
	3214	3/8	3/8		
Δ I	3215	3/8	1/2		
	3216	3/8	1/2		
	3220	1/2	5/8		

Catalog numbers indicate style and size of relief valve only - customer must specify pressure setting when ordering.

Important: A pressure relief valve is installed in a refrigeration system primarily to protect the receiver and is not intended to be an overload or high pressure cutout. Sherwood recommends that the pressure relief valve be set at the working pressure marked on the receiver, regardless of the type of refrigerant used.

* Not available in high-pressure settings.



